## **AMERICAN SPIRIT 5W-30 MOTOR OIL**

## **PRODUCT**

Multi-Grade Detergent Motor Oil


## **FEATURES**

**Energy Conserving:** Formulated with an advanced additive that reduces engine friction. This additive allows Marathon SAE 5W-30 to meet the requirements of an *Energy-Conserving* oil. An *Energy-Conserving* oil improves fuel economy.

**Easier Cold Engine Starting:** SAE 5W-30 provides the necessary film on engine parts to reduce friction and ease starting. *Energy Conserving* formulation enables the motor oil to flow faster through an engine at all temperatures.

**Advanced Detergent Package:** Holds sludge and deposits in suspension for a cleaner, longer-lasting engine.

**Approvals:** SAE 5W-30 meets quality specifications for API <u>Service SM and ILSAC GF-4</u>.





**API Service SM** 

**ILSAC GF-4** 

Products displaying the **API Donut** and the **ILSAC\* Starburst** meet the latest oil quality requirements of the automakers.

## **Applications**

Especially suitable for late model passenger cars requiring an SAE 5W-30 grade motor oil of API Service SM.

Warranty Validation: Meets engine requirements for newer domestic and foreign cars. Customers are assured that use of Marathon SAE 5W-30, as recommended by the manufacturer, will not void their vehicle's warranty.

Caution! Customers are advised to check the motor oil recommendations for their vehicles. Auto manufacturers recommend specific viscosity grades of motor oil for certain ambient temperature ranges. Use of a motor oil outside its recommended temperature range can cause lubrication related problems and lead to permanent engine damage. Marathon cannot be responsible for the misapplication of American Spirit 5W-30.

TYPICAL PROPERTIES	
	SAE 5W-30
Gravity, °API	33.03
Viscosity, cSt@40°C	61.2
cSt@100°C	10.5
Viscosity Index	158
Flash Point, COC, °C	220
Pour Point, °C	-39
Sulfated Ash, % Wt	0.80
Zinc, % Wt	0.083

<sup>\*</sup> International Lubricant Standardization and Approval Committee